



Clevis Sling Hook Green Pin® CSC

Product information

The sling hook can be used for general lifting applications. It can be quickly connected to the load lifting points thanks to its easy operating latch, which guarantees full safety. To connect simply push the latch, connect the hook to the lifting point, and release the latch. The forged latch guarantees a longer lifespan. It strongly limits the risk that the operator uses the hook without latch. The latch is fitted with a stainless steel spring and a sturdy pin. The clevis design enables a direct connection to grade 8 chain. The Green Pin® Sling Hook CL is available in a range to suit 5 mm up to 22 mm grade 8 chain.

Certification: At no extra charge this product can be supplied with a works certificate, a 3.1 material certificate and/or EC Declaration of Conformity.

Material: Alloy steel, quenched and tempered.

Marking: According to standard

Temperature range: -40°C up to +200°C

Finish: painted yellow (J), red (R) or white

Standard: EN 1677-2

Safety factor: 4:1

Grade: 8

| Part code | Chain dia range mm | WLL ton | a mm | b mm | c mm | d mm | e mm | f mm | g mm | h mm | i mm | Weight kg | Delivery time |
|--------------|-----------------------|------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--------------|---------------|
| 401300110460 | 6 | 1.12 | 76 | 7 | 27 | 15 | 19 | 28 | 73 | 108 | 8 | 0.29 | 10 |
| 401300200460 | 7-8 | 2 | 95 | 9 | 30 | 20 | 22 | 32 | 85 | 133 | 9 | 0.58 | 10 |
| 401300320460 | 10 | 3.2 | 113 | 11 | 33 | 24 | 28 | 42 | 106 | 164 | 13 | 1.1 | 2 |
| 401300540460 | 13 | 5.4 | 138 | 15 | 35 | 32 | 40 | 54 | 133 | 208 | 16 | 2.12 | 10 |
| 401300820460 | 16 | 8.2 | 161 | 18 | 43 | 40 | 44 | 67 | 165 | 240 | 20 | 3.67 | 10 |
| 401301280460 | 18-20 | 12.8 | 233 | 22 | 62 | 49 | 65 | 82 | 236 | 342 | 24 | 7.32 | 10 |
| 401301550460 | 22 | 15.5 | 235 | 24 | 77 | 54 | 60 | 96 | 227 | 343 | 28 | 10.63 | 10 |

Blueprint

