

## Swivel Sling Hook Green Pin® CSE

### Product information



The Green Pin® Sling Hook SE EN1677-2 is a grade 8 swivel sling hook with eye according to European standard for components for sling EN 1677-2. The sling hook can be used for general lifting applications. It can be quickly connected to the load lifting points thanks to its easy operating latch, which guarantees full safety. To connect simply push the latch, connect the hook to the lifting point, and release the latch. The forged latch guarantees a longer lifespan. It strongly limits the risk that the operator uses the hook without latch. The latch is fitted with a stainless steel spring and a sturdy pin. The large eye, designed with a flat enables an easy assembly on anti-rotating wire rope slings (with an omega link or with thimbles). These hooks are fitted with a needle roller thrust bearing. This enables smooth, easy rotation under load. The eye of the hook can also be connected to grade 8 chain with a connecting link or to a webbing with a web sling connector. The Green Pin® Sling Hook SE EN1677-2 is available in a range to suit 5/6 mm up to 18/20 mm grade 8 chain.

**Certification:** At no extra charge this product can be supplied with a works certificate, a 3.1 material certificate and/or EC Declaration of Conformity

... [Read more](#)

**Material:** Alloy steel, quenched and tempered.

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C

**Standard:** EN 1677-2


**Note:** Equipped with needle roller thrust bearing.

**Safety factor:** 4:1

**Grade:** 8

## Swivel Sling Hook Green Pin® CSE

### Blueprint



### Technical data

| Part code    | Chain dia range mm | WLL ton | a mm mm | b mm mm | c mm mm | d mm | e mm | f mm mm | g mm mm | h mm mm | i mm mm | j mm mm | Weight kg |
|--------------|--------------------|---------|---------|---------|---------|------|------|---------|---------|---------|---------|---------|-----------|
| 420500111390 | 5-6                | 1.12    | 100     | 33      | 32      | 27   | 15   | 19      | 72      | 164     | 12      | 6       | 0.54      |
| 420500201390 | 7-8                | 2       | 126     | 39      | 37      | 30   | 20   | 22      | 85      | 200     | 14      | 8       | 1         |
| 420500321390 | 10                 | 3.2     | 159     | 47      | 48      | 33   | 24   | 29      | 106     | 250     | 16      | 11      | 1.9       |
| 420500541390 | 13                 | 5.4     | 189     | 59      | 58      | 36   | 32   | 39      | 133     | 307     | 21      | 14      | 3.4       |
| 420500821390 | 16                 | 8.2     | 216     | 68      | 73      | 43   | 40   | 44      | 165     | 352     | 25      | 17      | 6.35      |