

## Anchorage Point PSA-YEP



### Product information



- Rotates through 360° adjustable in the direction of the load.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Passed 150 kg dynamic fall testing ( EU standard is 100 kg).
- Meets all requirements of the German BG BAU ( Employer-s insurance association of the building industry).
- Correspond to the European Directive for "personnel protection equipment" (89/686/EWG).
- PSA - Lifting point to be as an anchor point for personal protective equipment.

**Features:** Built-in RFID/NFC chip

**Material:** Manufactured from forged alloy steel, quenched and tempered

**Marking:** According to standard, number of persons, standards, individual serial number, manufacturer, production year, product ID

**Finish:** Yellow Painted

**Standard:** EN 795, EN 365, EN 50308

| Part code   | Max. number of persons | Torque Nm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | J mm | S mm | W mm | M mm       | Weight kg | Delivery time |
|-------------|------------------------|-----------|------|------|------|------|------|------|------|------|------|------|------|------------|-----------|---------------|
| 84158281007 | 1                      | 10        | 45   | 30   | 10   | 11   | 18   | 33   | 29   | 5    | 45   | 8    | 52   | M12 x 1.75 | 0.2       | 2             |
| 84158281015 | 2                      | 30        | 52   | 35   | 14   | 13   | 24   | 35   | 33   | 8    | 52   | 10   | 61   | M16 x 2    | 0.3       | 10            |
| 84158281023 | 2                      | 70        | 60   | 40   | 16   | 15   | 30   | 44   | 37   | 7    | 60   | 12   | 70   | M20 x 2.5  | 0.6       | 2             |

# Blueprint

