



## Clevis Sling Hook X-043/S Grade 10

### Product information

At least 25% greater WLL than traditional Grade 8 products.  
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.  
Tempering temperature minimum 400°C.  
Magnaflux crack detection is performed 100% on each batch.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-2

**Safety factor:** 4:1

**Grade:** 10

Part Code	WLL ton	EWL mm	For Grade 100 Chain mm	A mm	H mm	K mm	P1 mm	T mm	Weight kg	Delivery time
402300140700	1.4	79	6	7	18	79	23	15	0.3	10
402300250700	2.5	98	7, 8	9	22	98	27	18	0.6	10
402300400700	4	122	10	12	30	122	34	24	1.1	10
402300670700	6.7	147	13	15	37	147	44	30	2.3	10
402301000700	10	166	16	17	41	166	48	39	3.8	10
402301600700	16	207	20	24	64	207	57	48	8.7	10
402301900700	19	217	22	25	61	217	73	52	9.5	10

## Blueprint

