



Shortening Hook X-041

Product information

At least 25% greater WLL than traditional Grade 8 products.

Testing according to DIN PAS 1061 and ASTM A952/A 952M.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Tempering temperature minimum 400°C.

Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Painted.

Standard: EN 1677-1

Note: Not for use with Omega Link

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	A mm	B mm	F mm	G mm	K mm	P mm	Weight kg	Delivery time
402300140740	6	1.4	13	7	26	8	50	8	0.2	10
402300250740	7-8	2.5	16	10	30	9	62	10	0.3	10
402300400740	10	4	20	13	40	13	82	13	0.6	10
402300670740	13	6.7	26	16	52	16	107	17	1.4	10
402301000740	16	10	30	18	70	20	132	21	2.4	10
402301600740	20	16	40	22	73	24	148	24	4	10
402301900740	22	19	42	24	86	26	166	26	5	10
402302650740	26	26.5	50	30	110	32	207	33	10.1	10

Blueprint

