

## Eye Grab Hook X-041

### Product information



At least 25% greater WLL than traditional Grade 8 products.  
Testing according to DIN PAS 1061 and ASTM A952/A 952M.  
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.  
Tempering temperature minimum 400°C.  
Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Painted.

**Standard:** EN 1677-1


**Note:** Not for use with Omega Link

**Safety factor:** 4:1

**Grade:** 10

## Eye Grab Hook X-041

### Blueprint



### Technical data

Part code	Chain dia range mm	WLL ton	A mm	B mm	Fmm mm	Gmm mm	Kmm mm	Pmm mm	Weight kg	Delivery time
402300140740	6	1.4	13	7	26	8	50	8	0.2	2
402300250740	7-8	2.5	16	10	30	9	62	10	0.3	2
402300400740	10	4	20	13	40	13	82	13	0.6	2
402300670740	13	6.7	26	16	52	16	107	17	1.4	2
402301000740	16	10	30	18	70	20	132	21	2.4	2
402301600740	20	16	40	22	73	24	148	24	4	2
402301900740	22	19	42	24	86	26	166	26	5	2
402302650740	26	26.5	50	30	110	32	207	33	10.1	10