

Eye Grip self-locking Hook X-950

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Avoid finger injury by the grip design.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.


Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

Eye Grip self-locking Hook X-950

Blueprint



Technical data

Part code	Chain dia range mm	WLL ton	EWL mm	A mm	D mm	Hmm mm	Kmm mm	Omm mm	Pmm mm	Tmm mm	Wmm mm	Weight kg	Delivery time
402300400850	10	4	175	33	13	31	176	49	71	27	137	1.9	10
402300670850	13	6.7	227	40	16	39	226	64	80	34	174	4	2
402301000850	16	10	277	50	21	47	277	78	114	39	212	6.3	10
402301600850	20	16	329	62	23	55	329	92	127	54	251	12.3	2
402302000850	22	19	350	70	24	59	350	98	151	56	258	14	2