

Swivel Grip self-locking Hook X-952N

Product information



Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL. Magnaflux crack detection is performed 100% on each batch. Built with ball bearing and enables full swivel feature under load.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).


Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

Swivel Grip self-locking Hook X-952N

Blueprint



Technical data

Part code	Chain dia range mm	WLL ton	EWL mm	A mm	B mm	D mm	Hmm mm	Kmm mm	Omm mm	Pmm mm	Tmm mm	Wmm mm	Weight kg	Delivery time
420500400960	10	4	225	41	35	16	31	226	49	71	27	137	2.4	10
420500670960	13	6.7	285	46	44	21	39	283	64	80	34	174	5.2	10
420501000960	16	10	345	61	50	23	47	347	78	114	39	212	8.4	10
420501600960	20	16	433	74	82	25	55	433	92	127	54	251	14.5	10
420501900960	22	19	475	97	96	33	59	476	98	151	56	258	20.4	10