

Modular Spreader Beam MOD 70/70H

Product information

The standard range

Modular spreader beams provide the ideal solution for most lifting requirements – versatile and cost-effective. Modulift MOD 70 is available with capacity up to 70 t at 10.5 m and up to 14 m at a lower capacity. MOD 70H is available with capacity up to 100 t at 8.5 m and up to 14 m at a lower capacity.

[Click here to see the load v span chart for the standard range MOD 70](#)

[Click here to see the load v span chart for the standard range MOD 70H.](#)

The modular configuration and interchangeable components enable Modulift spreaders to be reused over many lifts. Designed by Modulifts engineering experts and manufactured in their own specialist facilities; the Modulift range are the leading modular spreader beams on the market.

How the spreader beam is configured

Every Modulift modular spreader beam consists of a pair of end units and a pair of drop links, with interchangeable struts that can be bolted into the assembly between the end units to either lengthen or shorten the beam to suit the requirements of the lift, making them reusable at different spans. The different components are shown in the table below. If you need help to configure your spreader beam, please contact us.

Load monitoring with Active Link


The innovative Active Link provides wireless real time data by measuring the load at either end of the spreader beam and is ideal for both weighing and dynamic load monitoring. Data is transmitted wirelessly to a USB transceiver that must be connected to a Windows computer or tablet with a spare USB port. The Active Link, which replaces the standard drop link component, offers myriad time, cost and weight advantages.

[... Read more](#)

We can offer Modulift Heavy Spreader Beams up to 1000 t. Contact us for more info about these beams.

Modular Spreader Beam MOD 70/70H

Blueprint



Technical data

Part code	Type	Weight kg
62080070DL035	Drop Link WLL 35t	17
62080070HDL050	Drop Link WLL 50t	32
62080070EU035	End Unit WLL 35t	56
62080070HEU050	End Unit WLL 50t	58
62080070050	0.50 m Strut	61
62080070100	1.0 m Strut	85
62080070200	2.0 m Strut	136
62080070400	4.0 m Strut	240
62080070AL35	AL70 Active link 35t	-
6208CMOD70	Set of 4 corners	-