



Insulated Swivel 8-088N

Product information



Insulated blank swivel for various lifting applications. Design for protection of overhead crane during welding operations on suspended loads. Individually tested to resist 1000 Volts insulated with Test Certificate.

For connection with suspension parts you will need Coupling Pin and C-Sleeve Set X-P015, please order them separately.

Order suspension parts Coupling Master Link 8-051.

2 pcs. half coupling links can be ordered as 1 pc. X-015 + 1 pc. X-P015.
Other suspension parts on request.

Features: Built-in RFID/NFC chip
Material: Quenched and tempered alloy steel
Marking: According to standard
Standard: EN 1677-1

Safety factor: 4:1
Grade: 8

| Part code | Chain diameter mm | WLL ton | D mm | L mm | W mm | Weight kg | Delivery time |
|--------------|----------------------|------------|---------|---------|---------|--------------|---------------|
| 422500200220 | 7 | 2 | 48 | 75 | 50 | 0.7 | 10 |
| 422500320220 | 10 | 3.15 | 58 | 97 | 62 | 1.3 | 10 |
| 422500530220 | 13 | 5.3 | 74 | 123 | 78.5 | 2.7 | 10 |
| 422500800220 | 16 | 8 | 90 | 143 | 95 | 4.7 | 10 |
| 422501250220 | 18 | 12.5 | 105 | 164 | 110 | 7 | 10 |

Blueprint

