

Round Sling POWERTEX PRS r-PET-y-test-18-feb

Product information



Material: Polyester (PES), high tenacity multifilament made from r-PET (recycled PET).

Marking: According to standard, CE-marked, UKCA-marked, The slings are provided with a blue label and a white warning label with Aspire range information on the back side.

Temperature range: -40°C up to +100°C

Standard: EN 1492-2

Note: Currently available in WLL 1t up to 5t and lengths 1 to 6 meter. Other variants on request

Warning: According to EN 1492-1:2000+A1:2008: D.3.7: Slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

Safety factor: 7:1

Round Sling POWERTEX PRS r-PET-y-test-18-feb

Technical data

Part code	Code	WLL ton	EWL m	Colour	Weight kg	Delivery time
340100100100330	09	1	1	violet	0.35	2
340100100200330	-	1	2	violet	0.7	2
340100100250330	-	1	2.5	violet	0.85	10
340100100300330	-	1	3	violet	1.05	2
340100100400330	-	1	4	violet	1.3	2
340100200100330	-	2	1	Green	0.55	2
340100200200330	-	2	2	Green	1.05	2
340100200300330	-	2	3	Green	1.45	2
340100200400330	-	2	4	Green	1.95	2
340100200600330	-	2	6	Green	2.65	10
340100300100330	-	3	1	yellow	0.6	2
340100300200330	-	3	2	yellow	1.15	2
340100300300330	-	3	3	yellow	2.05	2
340100300400330	-	3	4	yellow	2.6	2
340100300600330	-	3	6	yellow	3.7	10
340100500100330	-	5	1	Red	1.1	2
340100500200330	-	5	2	Red	2.4	2
340100500300330	-	5	3	Red	3.1	2
340100500400330	-	5	4	Red	4.1	2
340100500500330	-	5	5	Red	5.2	10