



# Round Sling POWERTEX PRS r-PET-y-test-11-jul

## Product information



POWERTEX Round slings PRS r-PET are made from high-strength **recycled** polyester (r-PET) yarn having a robust protective cover. Because it is made from r-PET yarn, this product **has up to 65% CO2 reduction\*** compared to the standard PRS round sling.

Because of this sustainability enhancement, this product is approved to be part of Lifting Solution Group's [Aspire range™](#). In November 2023, this product won the prestigious LEEA Sustainable Award.

**Sustainability Fact Sheet Available** (see tab documents drop-down menu)

The PRS r-PET slings are color coded for quick and easy identification of the Working Load Limit (WLL).

- Safe – All POWERTEX PRS r-PET slings are made from high-strength recycled polyester and tested in accordance with EN 1492-2
- Durable protective cover
- Each sling carries a blue label giving the correct WLL for different load connection methods and angles
- Each sling is marked with a unique serial number for safe sling registration
- Serial number is expressed both in a numeric format as well as Barcode for quick registration and maintenance
- Year/Month calendar printed on the label where the next inspection date can be marked or punched
- Printing on the blue label is protected by an additional transparent plastic layer for long life
- All round slings carry a white label showing a pictogram with important user warning instructions
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each sling

**Chemical resistance:** Resistant to most acids, but not strong alkalines.

**Stretch at working load:** 2-3%.

**Length tolerance:** Nominal length (EWL)  $\pm 2\%$ .

\*A 3rd party climate LCA with a cradle-to-gate perspective according to ISO14067 has shown that our r-PET round slings have up to 65% less CO2e emissions than our standard product. This means that our products are not only better for the environment but also make a positive contribution to reducing CO2 emissions.

**Material:** Polyester (PES), high tenacity multifilament made from r-PET (recycled PET).

**Marking:** According to standard, CE-marked, UKCA-marked, The slings are provided with a blue label and a white warning label with Aspire range information on the back side.

**Temperature range:** -40°C up to +100°C

**Standard:** EN 1492-2

**Note:** Currently available in WLL 1t up to 5t and lengths 1 to 6 meter. Other variants on request

**Warning:** According to EN 1492-1:2000+A1:2008: D.3.7: Slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

**Safety factor:** 7:1

Part code	WLL ton	EWL m	Colour	Weight kg	Delivery time
340100100100330	1	1	violet	0.35	2
340100100200330	1	2	violet	0.7	2
340100100250330	1	2.5	violet	0.85	10
340100100300330	1	3	violet	1.05	2
340100100400330	1	4	violet	1.3	2
340100200100330	2	1	Green	0.55	2
340100200200330	2	2	Green	1.05	2
340100200300330	2	3	Green	1.45	2
340100200400330	2	4	Green	1.95	2
340100200600330	2	6	Green	2.65	10
340100300100330	3	1	yellow	0.6	2
340100300200330	3	2	yellow	1.15	2
340100300300330	3	3	yellow	2.05	2
340100300400330	3	4	yellow	2.6	2
340100300600330	3	6	yellow	3.7	10
340100500100330	5	1	Red	1.1	2
340100500200330	5	2	Red	2.4	2
340100500300330	5	3	Red	3.1	2
340100500400330	5	4	Red	4.1	2
340100500500330	5	5	Red	5.2	10