

Round Sling POWERTEX PRS r-PET-y-test-18-feb

Product information



POWERTEX Round slings PRS r-PET are made from high-strength **recycled** polyester (r-PET) yarn having a robust protective cover. Because it is made from r-PET yarn, this product **has up to 65% CO2 reduction*** compared to the standard PRS round sling.

Because of this sustainability enhancement, this product is approved to be part of Lifting Solution Group's [Aspire range™](#). In November 2023, this product won the prestigious LEEA Sustainable Award.

Sustainability Fact Sheet Available (see tab documents drop-down menu)

The PRS r-PET slings are color coded for quick and easy identification of the Working Load Limit (WLL).

- Safe – All POWERTEX PRS r-PET slings are made from high-strength recycled polyester and tested in accordance with EN 1492-2
- Durable protective cover
- Each sling carries a blue label giving the correct WLL for different load connection methods and angles
- Each sling is marked with a unique serial number for safe sling registration
- Serial number is expressed both in a numeric format as well as Barcode for quick registration and maintenance
- Year/Month calendar printed on the label where the next inspection date can be marked or punched
- Printing on the blue label is protected by an additional transparent p ... [Read more](#)

Material: Polyester (PES), high tenacity multifilament made from r-PET (recycled PET).

Marking: According to standard, CE-marked, UKCA-marked, The slings are provided with a blue label and a white warning label with Aspire range information on the back side.

Temperature range: -40°C up to +100°C

Standard: EN 1492-2

Note: Currently available in WLL 1t up to 5t and lengths 1 to 6 meter. Other variants on request

Warning: According to EN 1492-1:2000+A1:2008: D.3.7: Slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

Safety factor: 7:1

Round Sling POWERTEX PRS r-PET-y-test-18-feb

Technical data

Part code	Code	WLL ton	EWL m	Colour	Weight kg
340100100100330	09	1	1	violet	0.35
340100100200330	-	1	2	violet	0.7
340100100250330	-	1	2.5	violet	0.85
340100100300330	-	1	3	violet	1.05
340100100400330	-	1	4	violet	1.3
340100200100330	-	2	1	Green	0.55
340100200200330	-	2	2	Green	1.05
340100200300330	-	2	3	Green	1.45
340100200400330	-	2	4	Green	1.95
340100200600330	-	2	6	Green	2.65
340100300100330	-	3	1	yellow	0.6
340100300200330	-	3	2	yellow	1.15
340100300300330	-	3	3	yellow	2.05
340100300400330	-	3	4	yellow	2.6
340100300600330	-	3	6	yellow	3.7
340100500100330	-	5	1	Red	1.1
340100500200330	-	5	2	Red	2.4
340100500300330	-	5	3	Red	3.1
340100500400330	-	5	4	Red	4.1
340100500500330	-	5	5	Red	5.2