

Webbing Sling with Eyes POWERTEX PWE r-PET

Product information



Material: Polyester (PES), high tenacity multifilament made from r-PET (recycled PET).

Marking: According to standard, CE-marked, UKCA-marked, The slings are provided with a blue label and a white warning label with Aspire range information on the back side.

Temperature range: -40°C up to +100°C

Standard: EN 1492-1

Note: According to EN 1492-1:2000+A1:2008: D.3.7: Slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

Safety factor: 7:1

Webbing Sling with Eyes POWERTEX PWE r-PET

Technical data

Part code	WLL ton	EWL m	Webbing width mm	Colour-	Colour	Weight kg	Packing Qty.	Delivery time
341100100100430	1	1	50	Violet	violet	0.25	7	2
341100100200430	1	2	50	-	violet	0.4	-	2
341100100300430	1	3	50	-	violet	0.6	-	2
341100100400430	1	4	50	-	violet	0.7	-	2
341100200100430	2	1	60	-	Green	0.45	-	2
341100200200430	2	2	60	-	Green	0.7	-	2
341100200300430	2	3	60	-	Green	1.1	-	2
341100200400430	2	4	60	-	Green	1.55	-	2
341100200600430	2	6	60	-	Green	2.25	-	2
341100300100430	3	1	90	-	yellow	0.75	-	2
341100300200430	3	2	90	-	yellow	1.1	-	2
341100300300430	3	3	90	-	yellow	1.6	-	2
341100300400430	3	4	90	-	yellow	2.35	-	2
341100300600430	3	6	90	-	yellow	3	-	10

key1

value1

key2

value2

key3

value3