

## Unilock Connecting Link U Pewag

---

### Product information



U Unilock connecting links are designed for the assembly of pewag chain slings. Special accessory in grade 8. UB bolts, UM safety nut and US washers are also separately available.

#### General connecting link for:

Master link - chain or rope, hook - chain or rope, chain - various securing eyes. Always ensure that the nut is not overtightened and that the bolt can rotate. Cannot be assembled to PW (PSW).

... [Read more](#)

---

**Material:** High duty grade 8.

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +100°C.

**Finish:** Red powder coated.


**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 8

## Unilock Connecting Link U Pewag

### Blueprint



### Technical data

Part code	Code	WLL ton	a mm mm	b mm mm	d mm	e mm	Mmm mm	smm mm	Weight kg
401200110060	U 5/6	1.12	16	21	9	34	7	11	0.07
401200150060	U 7	1.5	22	28	13	49	8	16	0.2
401200200060	U 8	2	22	28	13	48	10	16	0.22
401200320060	U 10	3.15	27	35	16	60	12	20	0.38
401200530060	U 13	5.3	34	39	18	72	16	24	0.67
401200800060	U 16	8	44	47	23	80	20	32	1.21
401201250060	U 19/20	12.5	52	56	26	96	24	36	1.97
401202120060	U 26	21.2	66	77	33	132	30	49	4.06