

Regular Swivel G-7723 - Jaw/Eye

Product information



The Green Pin[®] JE Swivel CP is a swivel with jaw-eye end-fittings and a split pin. The swivel is made from high tensile steel and can be used under water. Galvanization of the Green Pin[®] JE Swivel CP ensures its long-term durability. It is available in a range with a working load limit from 0.39 up to 20.5 ton.

Standard: Generally to RR-C-271, Type VII, Class 3.

Certification: Test certificates can be supplied upon request.

Material: High tensile steel, quenched and tempered.


Finish: Hot dipped galvanized.

Safety factor: 5:1

Grade: 3

Regular Swivel G-7723 - Jaw/Eye

Blueprint



Technical data

Part code	WLL ton	EWL mm	a mm mm	b mm mm	c mm mm	d mm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	Weight kg	Delivery time
422500040020	0.4	67	6	88	32	18	19	22	67	12	6	0.09	10
422500060020	0.6	75	8	99	41	21	25	23	75	13	8	0.16	10
422500110020	1.12	92	10	122	51	24	32	27	92	16	10	0.32	10
422500160020	1.63	114	13	154	64	33	38	33	115	21	13	0.57	10
422500240020	2.4	135	16	184	76	40	45	38	135	26	16	0.98	10
422500330020	3.3	154	19	211	89	45	51	45	154	31	19	1.88	10
422500450020	4.54	178	22	244	102	53	57	52	178	31	23	2.43	10
422500570020	5.7	217	25	297	114	59	64	72	218	47	29	4.02	10
422500820020	8.2	230	32	335	143	68	80	72	240	57	35	7.43	10
422502050020	20.5	364	38	534	198	110	122	116	381	78	51	22.1	10