



Short Link Lifting Chain POWERTEX PSL Grade 8

Product information

High-quality calibrated lifting chain intended for use in demanding applications like Grade 8 chain slings and chain lashings.

Features:

- Safe - each chain link is proof load tested 2,5 x WLL in the factory prior delivery
- Safe - each production batch is tested to meet the min. breaking force
- Ductile - Min. 20% elongation shall be achieved before failure
- Accurate - each length of chain is calibrated in the factory prior delivery
- Consistent – PSL chains are made in automatic chain welding machines
- Compliant - the chains fulfill EN 818-2 and the Machinery directive 2006/42/EC
- Each barrel includes a 14 language 2.2 Certificate and EC/UKCA Declaration of Conformity
- Each chain length carries a chain tag at the end for quick and positive identification
- The barrel is marked with an info sticker that allow quick and positive identification of the chain inside

Material: Quenched and Tempered Alloy Steel of Grade 8 quality (EN 818-2)

Marking: According to standard, CE-marked, UKCA-marked, Factory symbol, Grade 8, Traceability batch code marking

Temperature range: -40°C up to +200°C without reduction of WLL. Up to 400°C with reduction acc. to standard.

Finish: Black electrophoretic paint (RAL 9005).

Standard: EN 818-2

Safety factor: 4:1

Grade: 8

Part code	Chain diameter mm	WLL ton	Min. breaking force kN	Proof Load kN	d mm	p mm	W1	W2	Weight kg/m	Delivery time
203100600000200	6	1.12	45.2	28.3	6	18	7.8	22.2	0.8	10
203100800000200	8	2	80.4	50.3	8	24	10.4	29.6	1.5	2
203101000000200	10	3.15	126	78.5	10	30	13	37	2.3	2
203101300000200	13	5.3	212	133	13	39	16.9	48.1	3.9	2
203101600000200	16	8	322	201	16	48	20.8	59.2	5.8	2
203102000000200	20	12.5	503	314	20	60	26	74	8.9	2

Blueprint

