

Lifting Point POWERTEX LPS

Product information

The Powertex LPS with swivel eye redefines the capabilities of traditional lifting points. Engineered for demanding industrial environments that require reliability and efficiency, the Powertex LPS has a dynamic **360-degree rotation feature** and an impressive 4.5 times increase in Working Load Limit (WLL) compared to conventional DIN580 lifting points. Its design incorporates a robust forged swivel eye, complemented by a bolt and washer assembly, which ensures secure and versatile lifting operations. The bolt features a hex socket cap grip for easy installation, allowing for swift mounting with standard tools. It includes a supplementary 'quick key' for manual tightening during temporary setups.

Allowed loading directions:

- Straight (max WLL)
- Sideways (not perpendicular to the eye)
- 180 degrees in the plane of the eye (+/- 90 degrees from centre line)

Product Features:

- Durable Finish: Coated in PURE RED powder paint, the Powertex LPS lifting points are visually distinct and offer superior resistance to wear and corrosion.
- Compliance to standard: Manufactured to meet the testing requirements specified by EN 1677-1, ensuring high safety and quality standards.
- Reliable: Designed with a safety factor of at least 4 in the intended load directions, offering a secure lifting experience.
- Quality assurance: Each component undergoes crack detection testing in the factory and forged links are proof load tested to ensure reliability.

[... Read more](#)

Features: 360 degrees rotatable

Material: Forged alloy steel

Marking: According to standard, CE-marked, UKCA-marked, POWERTEX or PX, model name, WLL and batch number

Temperature range: -40°C up to +200°C

Finish: Powder painted in PURE RED

Standard: EN 1677-1

Note: Before use, review the WLL diagram to select the correct LPS for your application

Safety factor: 4:1

Lifting Point POWERTEX LPS

[Blueprint](#)
[Technical data](#)

| Part code | WLL ton | Thread mm | Model | Torque Nm | A mm | B mm | C mm | D mm | Emm mm | Fmm mm | Weight kg |
|------------|---------|-----------|---------|-----------|-------|------|------|------|--------|--------|-----------|
| 4215LPSM8 | 0.3 | M8 | LPS-M8 | 6-10 | 38 | 26 | 45.3 | 11.5 | 25 | 8 | 0.11 |
| 4215LPSM10 | 0.4 | M10 | LPS-M10 | 6-10 | 38 | 26 | 45.3 | 14 | 25 | 8 | 0.12 |
| 4215LPSM12 | 0.75 | M12 | LPS-M12 | 10-15 | 43.5 | 32 | 54 | 17 | 33 | 10 | 0.2 |
| 4215LPSM16 | 1.5 | M16 | LPS-M16 | 20-30 | 52 | 37.5 | 63.5 | 24 | 36 | 14 | 0.35 |
| 4215LPSM20 | 2.3 | M20 | LPS-M20 | 50-70 | 63 | 44.5 | 78.5 | 30 | 47.5 | 20.6 | 0.66 |
| 4215LPSM24 | 3.2 | M24 | LPS-M24 | 120-150 | 74 | 51.6 | 92 | 35.3 | 53 | 20 | 1.1 |
| 4215LPSM30 | 4.5 | M30 | LPS-M30 | 200-250 | 92 | 65 | 118 | 45 | 68 | 24 | 2.1 |
| 4215LPSM36 | 7 | M36 | LPS-M36 | 280-400 | 105 | 76 | 136 | 56.8 | 82 | 30 | 4 |
| 4215LPSM42 | 9 | M42 | LPS-M42 | 400-500 | 121.5 | 88 | 160 | 66.5 | 92 | 35 | 5.5 |
| 4215LPSM48 | 12 | M48 | LPS-M48 | 400-500 | 138 | 100 | 180 | 75.5 | 110 | 42 | 8.9 |