



## Fall Arrest Block IKAR Flexible HWB 2,0 DWX

### Product information

Fall arrest block double with webbing and swivel suspension, which prevents the webbing from twisting. Integrated energy-absorber and retractable lanyard.

Seawater-resistant aluminum housing with retractable lanyard made of almost indestructible Dyneema® webbing.

Approved for vertical and horizontal use.

**Edge tested:** Tested at sharp edges,  $R \geq 0,5 \text{ mm}$  (CNB/P/11.060 2008 sharp edge Type A)

**Carabiner:** IKV 32 with opening width 66 mm in the bottom

**Shock absorbtion:** Max. shock impact  $< 4 \text{ kN}$ .

**Material:** Housing: aluminium, webbing: Dyneema®

**Marking:** According to standard

**Temperature range:**  $-40^{\circ}\text{C}$  up to  $+50^{\circ}\text{C}$

**Finish:** Blue painted

**Standard:** EN 360

| Part code    | Code         | Max. number of persons | Length m | Max load kg | B mm | L mm | T mm | Weight kg | Delivery time |
|--------------|--------------|------------------------|----------|-------------|------|------|------|-----------|---------------|
| 822100250660 | HWB 2,0 DW X | 1                      | 2.5      | 136         | 170  | 425  | 67   | 2.2       | 2             |

Blueprint

