



Round Sling EXTREEMA® XS

Product information

The XS round slings are the ultimate solution for lifting loads ranging from 1T to 20T. They offer a cost-effective and reliable alternative to traditional polyester slings. Say goodbye to the hassle of disposal, storage, and transportation costs, and welcome a practical and efficient choice that never compromises safety and quality.

Their lightweight design ensures easy handling and transport, making them a practical choice across various lifting applications. By embracing the XS round slings, industries secure a dependable lifting solution and embark on a sustainable journey, reducing industrial waste and minimizing their environmental footprint.

Extreema XS Slings have massive lifting power in a much smaller size with 78% less weight than polyester round slings and 55% smaller diameter, you can lift on the shackle pin. Slings are 8-10 times lighter than steel wire ropes.

Features and benefits:

- Saving costs
- D:d ratio of 1:1
- Environmentally friendly
- Light in weight
- Flexible
- Less storage
- Long life cycle
- Access to limited lifting space
- Safer lifting operations
- Improving workflow
- Available in 3t yellow, 5t red, 10t orange, 15t orange and 20t orange
- Available in effective working lengths in the range of 0.5 m up to 16 m

Material: HMPE -Dyneema®

Marking: According to standard, CE-marked

Temperature range: -50°C up to +70°C

Standard: EN 1492-2

except material

Safety factor: 7:1

| Part code | WLL ton | EWL m | Colour | Delivery time |
|-----------------|------------|----------|--------|---------------|
| 340500300050030 | 3 | 0.5 | yellow | 10 |
| 340500300080030 | 3 | 0.75 | yellow | 10 |
| 340500300100030 | 3 | 1 | yellow | 10 |
| 340500300150030 | 3 | 1.5 | yellow | 10 |
| 340500300200030 | 3 | 2 | yellow | 10 |
| 340500300250030 | 3 | 2.5 | yellow | 10 |
| 340500300300030 | 3 | 3 | yellow | 10 |
| 340500300400030 | 3 | 4 | yellow | 10 |
| 340500300500030 | 3 | 5 | yellow | 10 |
| 340500500050030 | 5 | 0.5 | Red | 10 |
| 340500500100030 | 5 | 1 | Red | 10 |
| 340500500150030 | 5 | 1.5 | Red | 10 |
| 340500500200030 | 5 | 2 | Red | 10 |
| 340500500250030 | 5 | 2.5 | Red | 10 |
| 340500500300030 | 5 | 3 | Red | 10 |
| 340500500400030 | 5 | 4 | Red | 10 |
| 340500500500030 | 5 | 5 | Red | 10 |
| 340501000150030 | 10 | 1.5 | Orange | 10 |
| 340501000200030 | 10 | 2 | Orange | 10 |
| 340501000300030 | 10 | 3 | Orange | 10 |
| 340501000400030 | 10 | 4 | Orange | 2 |
| 340501000500030 | 10 | 5 | Orange | 10 |

Technical data