



## Vacuum Lifting Beam CLAD-MAN®

### Product information



moving limits

The CLAD-MAN® vacuum lifting beam is the all-rounder for XXL jobs at the construction site. The vacuum lifting beam makes the mounting easier and increases the safety and the efficiency substantial.

#### Suitable for lifting of:

- Panels up to 26 meters long
- Trapezoidal elements
- Roof and wall elements weighing up to 800 kg
- Rotatable by up to 90°
- Roof slope up to 45°

#### An all-round tool...

CLAD-MAN® is designed for outdoor as well as indoor use and can be used together with a crane, telescope loading machine, truck or similar. The lifting beam works without power connection due to the built-in batteries with integrated charger.

Thanks to the 2-circuit system, the digital vacuum sensor technology and optional belt safety system, CLAD-MAN® delivers maximum safety for personnel and materials under harsh on-site conditions. The unique belt system allows for very fast and safe placement of the belts.

The vacuum-actuated pump control (Ecomatic) makes sure that the batteries are taken good care of. A long workday on site poses a great challenge for personnel and equipment. You can rely on CLAD-MAN®'s consistent level of performance and intelligent energy management.

The modular design with the wide variety of option packs offers the right solution for every application. CLAD-MAN® is the ideal partner when it is necessary to install especially long wall or roof panels or heavy trapezoidal sheets on sloped roofs with a pitch of up to 45°.

#### Product variants

The CLAD-MAN vacuum lifter is available in different versions with:

- horizontal load capacities from 400 to 800 kg
- vertical load capacities from 400 to 800 kg
- 8 to 16 suction plates
- different lifting beam lengths, etc.

We will happily advise you on selecting a suitable device for your application.

| Part Code   | WLL ton | Model                   | WLL Vertical ton | B SPL mm | L SPL mm | EH mm | L mm   | Weight kg | Delivery time |
|-------------|---------|-------------------------|------------------|----------|----------|-------|--------|-----------|---------------|
| 56051031992 | 0.4     | CLAD-MAN-D-400/8L/16000 | -                | 140      | 650      | 1,280 | 16,000 | 570       | 10            |
| 56051031991 | 0.6     | CLAD-MAN-D-600/8L/4000  | 0.4              | 140      | 650      | 1,280 | 4,000  | 370       | 10            |
| 56051031990 | 0.8     | CLAD-MAN-D-800/12L/3000 | 0.6              | 140      | 650      | 1,280 | 3,000  | 400       | 10            |
| 56051031993 | 0.8     | CLAD-MAN-W-800/16L/3000 | 0.8              | 140      | 650      | 1,280 | 3,000  | 475       | 10            |

### Blueprint