

Swageless Terminal with Eye

Product information



Swageless stainless eye terminal for safe, reliable and machine free self assembly
... [Read more](#)



Material: Stainless steel AISI 316.


Temperature range: -50°C to +100°C and briefly up to +200°C

Finish: High polished.

Warning: Read assembly instructions before use!

Swageless Terminal with Eye

Blueprint



Technical data

| Part code | Rope Ø range mm | MBL ton | Wire Ø inch | A mm | D mm | L1mm mm | L2mm mm | KW1 mm | KW2 mm | Weight kg/100pc |
|------------|-----------------|---------|-------------|------|------|---------|---------|--------|--------|-----------------|
| 1207821903 | 3 | 0.75 | 1/18" | 5,5 | 6.5 | 58.6 | 50.1 | 13 | 12 | 4 |
| 1207821904 | 4 | 1.5 | 5/32" | 7 | 8.5 | 71.4 | 60.4 | 13 | 14 | 7.3 |
| 1207821905 | 5 | 2.18 | - | 8 | 10.5 | 81.5 | 69.5 | 17 | 16 | 9.8 |
| 1207821906 | 6 | 3.7 | 1/4" | 9 | 13 | 96 | 82 | 19 | 19 | 15 |
| 1207821907 | 7 | 4.7 | 9/32" | 9 | 13.2 | 105 | 89.5 | 22 | 22 | 21.2 |
| 1207821908 | 8 | 5.6 | 5/16" | 10 | 14.5 | 117 | 100.5 | 24 | 24 | 28.1 |
| 1207821910 | 10 | 8.3 | - | 13 | 16.2 | 137 | 117 | 27 | 27 | 46 |
| 1207821912 | 12 | 12 | - | 15 | 19.5 | 161 | 139.5 | 32 | 32 | 72 |
| 1207821914 | 14 | 14 | - | 18 | 23 | 187.6 | 161.6 | 36 | 36 | 110 |