

Lifting Beam Type K

Product information

CERTEX

This type of lifting beam is characterized by adjustable attachments via a cam beam and it is designed for direct attachment to the crane hook in the central lifting eye. The attachment points are designed as oval rings, which makes it possible to use for example a 2-part sling. Other lengths and working loads can be manufactured upon request.

Design: Lightweight welded pipe beam construction providing good torsional stiffness.

Proof load: Usually 1,5 x WLL.

[... Read more](#)

Material: Hollow beam and plate manufactured with high-strength structural steel.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Note: Top sling, separate slings and other accessories to be ordered separately.

Safety factor: 1,5 x WLL

Lifting Beam Type K

Blueprint



Technical data

| Part code | Code | WLL ton | B mm | Hmm mm | L min. mm mm | L max. mm mm | Weight kg |
|---------------|-----------|---------|------|--------|--------------|--------------|-----------|
| 6205620051500 | K-0,5/1,5 | 0.5 | 95 | 250 | 750 | 1,500 | 28 |
| 6205620052000 | K-0,5/2 | 0.5 | 95 | 250 | 800 | 2,000 | 34 |
| 6205620052500 | K-0,5/2,5 | 0.5 | 95 | 250 | 1,300 | 2,500 | 38 |
| 6205620053000 | K-0,5/3 | 0.5 | 95 | 250 | 1,350 | 3,000 | 58 |
| 6205620053500 | K-0,5/3,5 | 0.5 | 120 | 280 | 1,850 | 3,500 | 72 |
| 6205620054000 | K-0,5/4 | 0.5 | 120 | 280 | 1,900 | 4,000 | 81 |
| 6205620055000 | K-0,5/5 | 0.5 | 120 | 280 | 2,450 | 5,000 | 139 |
| 6205620056000 | K-0,5/6 | 0.5 | 140 | 330 | 3,000 | 6,000 | 172 |
| 6205620101500 | K-1/1,5 | 1 | 120 | 280 | 750 | 1,500 | 32 |
| 6205620102000 | K-1/2 | 1 | 120 | 280 | 800 | 2,000 | 48 |
| 6205620102500 | K-1/2,5 | 1 | 120 | 280 | 1,300 | 2,500 | 56 |
| 6205620103000 | K-1/3 | 1 | 120 | 280 | 1,350 | 3,000 | 65 |
| 6205620103500 | K-1/3,5 | 1 | 120 | 280 | 1,850 | 3,500 | 101 |
| 6205620104000 | K-1/4 | 1 | 140 | 330 | 1,900 | 4,000 | 146 |
| 6205620106000 | K-1/6 | 1 | 156 | 415 | 3,000 | 6,000 | 169 |
| 6205620105000 | K-1/5 | 1 | 140 | 330 | 2,450 | 5,000 | 177 |
| 6205620201500 | K-2/1,5 | 2 | 140 | 330 | 750 | 1,500 | 48 |
| 6205620202000 | K-2/2 | 2 | 140 | 330 | 800 | 2,000 | 56 |
| 6205620202500 | K-2/2,5 | 2 | 140 | 330 | 1,300 | 2,500 | 74 |
| 6205620203000 | K-2/3 | 2 | 140 | 330 | 1,350 | 3,000 | 98 |
| 6205620203500 | K-2/3,5 | 2 | 140 | 330 | 1,850 | 3,500 | 132 |
| 6205620204000 | K-2/4 | 2 | 156 | 415 | 1,900 | 4,000 | 135 |

Lifting Beam Type K

Technical data

| Part code | Code | WLL ton | B mm | Hmm mm | L min. mm mm | L max. mm mm | Weight kg |
|---------------|---------|---------|------|--------|--------------|--------------|-----------|
| 6205620205000 | K-2/5 | 2 | 156 | 415 | 2,450 | 5,000 | 207 |
| 6205620206000 | K-2/6 | 2 | 156 | 415 | 3,000 | 6,000 | 253 |
| 6205620301500 | K-3/1,5 | 3 | 145 | 417 | 600 | 3,000 | 58 |
| 6205620302000 | K-3/2 | 3 | 156 | 415 | 800 | 2,000 | 74 |
| 6205620303000 | K-3/3 | 3 | 156 | 415 | 1,350 | 3,000 | 115 |
| 6205620304000 | K-3/4 | 3 | 156 | 415 | 1,900 | 4,000 | 174 |
| 6205620305000 | K-3/5 | 3 | 106 | 455 | 2,450 | 5,000 | 246 |
| 6205620306000 | K-3/6 | 3 | 250 | 595 | 3,000 | 6,000 | 408 |
| 6205620502000 | K-5/2 | 5 | 106 | 455 | 800 | 2,000 | 106 |
| 6205620503000 | K-5/3 | 5 | 106 | 455 | 1,350 | 3,000 | 165 |
| 6205620504000 | K-5/4 | 5 | 106 | 455 | 1,900 | 4,000 | 245 |
| 6205620505000 | K-5/5 | 5 | 250 | 595 | 2,450 | 5,000 | 258 |
| 6205620506000 | K-5/6 | 5 | 250 | 595 | 3,000 | 6,000 | 409 |
| 6205620802000 | K-8/2 | 8 | 106 | 455 | 800 | 2,000 | 123 |
| 6205620803000 | K-8/3 | 8 | 250 | 595 | 1,350 | 3,000 | 250 |
| 6205620804000 | K-8/4 | 8 | 250 | 595 | 1,900 | 4,000 | 352 |
| 6205620805000 | K-8/5 | 8 | 250 | 595 | 2,450 | 5,000 | 495 |
| 6205620806000 | K-8/6 | 8 | 280 | 760 | 3,000 | 6,000 | 600 |
| 6205621002000 | K-10/2 | 10 | 250 | 595 | 800 | 2,000 | 266 |
| 6205621003000 | K-10/3 | 10 | 250 | 595 | 1,350 | 3,000 | 330 |
| 6205621004000 | K-10/4 | 10 | 250 | 595 | 1,900 | 4,000 | 383 |
| 6205621005000 | K-10/5 | 10 | 280 | 760 | 2,450 | 5,000 | 522 |
| 6205621006000 | K-10/6 | 10 | 280 | 760 | 3,000 | 6,000 | 704 |
| 6205621604000 | K-16/4 | 16 | 280 | 760 | 1,900 | 4,000 | 517 |
| 6205621605000 | K-16/5 | 16 | 330 | 825 | 2,450 | 5,000 | 741 |