

## Lifting Beam Type H-SSB

### Product information



### CERTEX

This type of lifting beam has adjustable attachment points in both directions and is based on lifting in four points. The lifting beam is designed for direct attachment with the crane hook in the central lifting eye. The attachment point is designed as an oval ring, which makes it possible to use for example a 2-part sling. Other lengths and working loads can be manufactured upon request.

**Design:** Lightweight welded beam construction providing good torsional stiffness.

**Proof load:** Usually 1,5 x WLL.

**Material:** Beam and plate of high-strength structural steel.


**Marking:** Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

**Finish:** Yellow painted. Other treatments available on request.

**Note:** Top sling, separate slings and other accessories to be ordered separately.

## Lifting Beam Type H-SSB

### Blueprint



### Technical data

Part code	Code	WLL ton	Hmm mm	L1 min. mm mm	L1 max. mm mm	L2 min. mm mm	L2 max. mm mm	Weight kg	Delivery time
62056430051500	H-SSB-0,5/2-1,5	0,5	205	1,200	2,000	750	1,500	112	35
62056430052000	H-SSB-0,5/3-2	0,5	205	1,800	3,000	800	2,000	146	35
62056430052500	H-SSB-0,5/4-2,5	0,5	205	2,400	4,000	1,300	2,500	174	35
62056430151500	H-SSB-1,5/2-1,5	1,5	240	1,200	2,000	750	1,500	142	35
62056430152000	H-SSB-1,5/3-2	1,5	240	1,800	3,000	800	2,000	183	35
62056430152500	H-SSB-1,5/4-2,5	1,5	240	2,400	4,000	1,300	2,500	221	35
62056430301500	H-SSB-3/2-1,5	3	300	1,200	2,000	750	1,500	192	35
62056430302000	H-SSB-3/3-2	3	300	1,800	3,000	800	2,000	241	35
62056430302500	H-SSB-3/4-2,5	3	300	2,400	4,000	1,300	2,500	286	35
62056430501500	H-SSB-5/2-1,5	5	315	1,200	2,000	750	1,500	276	35
62056430502000	H-SSB-5/3-2	5	315	1,800	3,000	800	2,000	369	35
62056430502500	H-SSB-5/4-2,5	5	315	2,400	4,000	1,300	2,500	480	35
62056430801500	H-SSB-8/2-1,5	8	425	1,200	2,000	750	1,500	553	35
62056430802000	H-SSB-8/3-2	8	425	1,800	3,000	800	2,000	653	35
62056430802500	H-SSB-8/4-2,5	8	425	2,400	4,000	1,300	2,500	802	35
62056431001500	H-SSB-10/2-1,5	10	540	1,200	2,000	750	1,500	837	35
62056431002000	H-SSB-10/3-2	10	540	1,800	3,000	800	2,000	989	35
62056431002500	H-SSB-10/4-2,5	10	540	2,400	4,000	1,300	2,500	1,135	35