

Helicopter Beam X-Duplex

Product information



CERTEX

This type of lifting beam is designed as a folding crossbeam. The lifting beam is designed with one pullout per arm allowing the attachment points to be adjusted in the length/width. A 4-part sling must be used between the lifting beam and the crane hook. Other lengths and working loads can be manufactured upon request.

Design: Lightweight welded beam construction providing good torsional stiffness.

Proof load: Usually 1,5 x WLL.


Material: Beam and plate of high-strength structural steel.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Note: Top sling, separate slings and other accessories to be ordered separately.

Helicopter Beam X-Duplex

[Blueprint](#)[Technical data](#)

| Part code | WLL ton | Type | L min. mm mm | L max. mm mm | L1 max. mm mm | Weight kg | Delivery time |
|----------------|---------|------------|--------------|--------------|---------------|-----------|---------------|
| 62056502503400 | 2.5 | Duplex 2.5 | 3,600 | 4,800 | 3,400 | 159 | 35 |
| 62056506003400 | 6 | Duplex 6 | 3,700 | 4,800 | 3,400 | 199 | 35 |
| 62056510003400 | 10 | Duplex 10 | 3,700 | 4,900 | 3,500 | 279 | 35 |
| 62056520003400 | 20 | Duplex 20 | 3,700 | 4,900 | 3,500 | 492 | 35 |