

Helicopter Beam X-Triplex

Product information

CERTEX

This type of lifting beam is designed as a folding crossbeam. The lifting beam is designed with a double pullout per arm, allowing the attachment points to be adjusted in the length/width. A 4-part sling must be used between the lifting beam and the crane hook. Other lengths and working loads can be manufactured upon request.

Design: Lightweight welded beam construction providing good torsional stiffness. TRIPLEX model K is special designed to fit in the side direction of a truck.

Proof load: Usually 1,5 x WLL.



Material: Beam and plate of high-strength structural steel.


Marking: CE-marked, Working load limit (WLL), manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Note: Top sling, separate slings and other accessories to be ordered separately.

Helicopter Beam X-Triplex

Blueprint



Technical data

Part code	WLL ton	Type	L min. mm mm	L max. mm mm	L1 max. mm mm	Weight kg	Delivery time
62056502504200	2.5	Triplex 2,5	3,600	6,000	4,300	196	35
62056506004510	6	Triplex 6K*	4,000	6,400	4,500	197	35
62056506004500	6	Triplex 6	2,300	4,700	3,300	239	35
62056510004510	10	Triplex 10K*	2,250	4,400	3,200	285	35
62056510004500	10	Triplex 10	3,900	6,500	4,500	343	35
62056520004510	20	Triplex 20K*	4,000	6,400	4,600	465	35
62056520004500	20	Triplex 20	2,250	4,400	3,200	591	35