

Swivel Jaw / Eye Crosby S3

Product information



Design: Swivel with jaw and eye equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- All jaws complete with bolts, nuts and cotter pins.
- Other types and capacities up to 1250t available on demand.

... [Read more](#)

Marking: CE-marked


Note: Always check before use if your steel wire rope is suitable for use with a swivel.

Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1

Swivel Jaw / Eye Crosby S3

Blueprint



Technical data

Part code	Rope Ø range mm	WLL ton	Swivel No	C mm	Gmm mm	Hmm mm	Jmm mm	Kmm mm	Nmm mm	Omm mm	Qmm mm	Rmm mm	S mm	Tmm mm	Weight kg
422500300090	13	3	3-S-3	237	70	19.1	22.4	41.1	33.3	25.4	19.1	26.2	28.4	31.8	4.14
422500500090	16	5	5-S-3	256	76	22.4	25.4	57	41.1	28.4	25.4	32.5	31.8	31.8	6.12
422500850090	19	8.5	8-S-3	311	102	25.4	39.5	71.5	54	35.1	31.8	35.8	41.1	38.1	11.3
422501500090	26	15	15-S-3	425	127	38.1	44.5	86	89	44.5	49.3	51.5	70	54	27.7