



Special Master Link Assembly Pewag VAW

Product information

VAW For pewag connex and welded system. For assembling 3- and 4-leg chains with connex links CW, when shortening hooks are to be assembled separately, and for slings with thimbled eyes.

For use in rope slings please consider that load capacity is listed according to EN 1677-4 with safety factor 4.

For assembling of welded slings with BW by pewag.

Material: High duty grade 10

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type

Temperature range: -40°C up to +380°C

Finish: Orange powder coated

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

| Part code | Code | WLL ton | EWL | Consisting of | Use for hook DIN15401 Nr | Double hook DIN 15402 no. | e mm | t mm | w mm | Weight kg | Delivery time |
|--------------|-----------|------------|-----|-----------------|--------------------------|---------------------------|---------|---------|---------|--------------|---------------|
| 402104110330 | VAW 19/20 | 41.1 | 625 | AW 50 + 2 MW 36 | 32 | 40 | 625 | 350 | 190 | 31.51 | 2 |
| 402104740330 | VAW 22 | 47.4 | 690 | AW 50 + 2 AW 45 | 32 | 40 | 690 | 350 | 190 | 42.19 | 10 |
| 402105800330 | VAW 26 | 58 | 750 | AW 56 + 2 AW 50 | 32 | 40 | 750 | 400 | 200 | 56.4 | 10 |
| 402108500330 | VAW 32 | 85 | 860 | AW 72 + 2 AW 56 | 50 | 63 | 860 | 460 | 250 | 99.02 | 10 |

Blueprint

