



## Fork Hook Pewag GHW

### Product information

GHW Fork hooks are designed for the assembling of chain slings. They serve for lifting and transporting sheet, metal stacks, boards and frames.

For lifting large sheet metal stacks and boards. Use only in pairs.

**Recommended angle of inclination of the sling:**  $\beta$  30-45°.

**Material:** High duty grade 10.

**Marking:** According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

**Temperature range:** -40°C up to +380°C.

**Finish:** Orange powder coated.

**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 10

| Part code    | Code    | WLL<br>ton | EWL | BW-link | b<br>mm | d<br>mm | e<br>mm | g<br>mm | s<br>mm | Weight<br>kg | Delivery time |
|--------------|---------|------------|-----|---------|---------|---------|---------|---------|---------|--------------|---------------|
| 402300140590 | GHW 5/6 | 1.4        | 203 | BW 13   | 190     | 23      | 203     | 65      | 100     | 2.84         | 10            |
| 402300250590 | GHW 7/8 | 2.5        | 300 | BW 16   | 254     | 30      | 300     | 100     | 150     | 7.25         | 10            |
| 402300400590 | GHW 10  | 4          | 402 | BW 22   | 380     | 40      | 402     | 130     | 200     | 16           | 10            |

## Blueprint

